

TechSpecs

421 N. Roosevelt St. Kennewick, WA 99336 TEL: 509-544-0720

On the Leading Edge of Sensing Technology

www.uniwest.com info@uniwest.com FAX: 509-544-0868

O

ECS-5 Bolt Hole Scanner Extended Scan Depth

P/N: 99978-4.0

Ideal for both rotary and linear scan-motion indexing.

12.15 oz-in

ECS-5 Specifications

- Speed:
- Stall Torque:
- Scan Depth:
- Frequency Range:
- Weight:
- Overall Size:
- Nose Size:
- Probe to Nose:
- Probe Type:
- Probe Diameter:
- Probe Connector:
- Coil Types:
- Signal Coupling:

Instrument Compatibility

UniWest EVⁱ

Cable (sold separately)

- Part Number:
- Removable:
- Connector:
- Length:

35 KHz - 6 MHz 19.2 oz

4.0" with 0.01" resolution

5.15" x 1.72" x 3.62" (L x W x H)

250 - 3800 RPM, constant torque

- 1.23" x 1.25" x 6.23" (L x W x H)
- 0.55″
- UniWest SSB
- ter: 0.13 0.75"
 - 4-pin Fischer[®] with O-rings
 - Absolute & Differential in Reflection or Bridge
 - Rotary Transformer

74191

10 feet

27-pin Fischer®

Yes

Controls

• Rotate / Start Auto

ANNER

- Probe Eject
- Jog Down
- Jog Up
- Red LED (Traveling Up)
- Green LED (Traveling Down)

