

# **TechSpecs**

421 N. Roosevelt St. Kennewick, WA 99336

On the Leading Edge of Sensing Technology

www.uniwest.com

info@uniwest.com FAX: 509-544-0868

**ECS-5s Bolt Hole Scanner** 

**Extended Scan Depth** P/N: 100060-4.0

Ideal for both rotary and linear scan-motion indexing.

#### **ECS-5 Specifications**

Speed: 250 - 3800 RPM, constant torque

**Stall Torque:** 12.15 oz-in

4.0" with 0.01" resolution Scan Depth:

25 Hz - 6 MHz **Frequency Range:** 

Weight: 19.2 oz

**Overall Size:** 5.14" x 1.72" x 7.10" (L x W x H) **Nose Size:** 1.10" x 1.25" x 7.10" (L x W x H)

**Probe to Nose:** 0.55"

**Probe Type: UniWest SSB Probe Diameter:** 0.13 - 0.75"

**Probe Connector:** 4-pin Fischer® with O-rings Absolute & Differential in **Coil Types:** 

Reflection or Bridge

**Signal Coupling:** Slip Ring

## **Instrument Compatibility**

UniWest EV<sup>i</sup>

#### **Cable** (sold separately)

**Part Number:** 74191 Removable: Yes

**Connector:** 27-pin Fischer®

Length: 10 feet

### **Controls**

- Rotate / Start Auto
- Probe Eject
- Jog Down
- Jog Up
- Red LED (Traveling Up)
- Green LED (Traveling Down)



