

64 Channel Handheld Array Scanner P/N 100701



- Removable Probe Heads (sold separately)
 - US-4546 Probe Head, Absolute 64 Array Coil, 200 kHz, 2.44" Coverage
 - US-4547 Probe Head, Absolute 64 Coil, 2 MHz, 2.44" Coverage
 - US-4548 Probe Head, Absolute 40 Coil, 1-10 kHz, 2.40" Coverage
 - US-4579 Probe Head, Absolute 16 Coil, 1 kHz, 2" Coverage
- Integrated multiplexing
- Integrated encoder with wheels
- Encoder resolution: 1684 counts per inch (.0005 inch per count)
- Null and Clear Buttons
- Probe Connector: 12pin Lemo
- Weight: 1lb 0.5oz, 1lb 2.2oz with coil pack
- Compatible with UniWest EVi

Cable sold separately:

EVi: 75915-XX, 27p Fischer to 12p Lemo, (XX ft.)

Calibration Standards sold separately:

78238: Calibration Std Holder, for 100701 ECA-64 Handheld Array Scanner

78228-1: Calibration Standard, Aluminum 7075-T651

78228-2: Calibration Standard, Steel 4340 Alloy

78228-3: Calibration Standard, Titanium 6AL4V

78228-4: Calibration Standard, Aluminum 6061-T6

78228-5: Calibration Standard, Inconel 718